VersaTREK Instrument Specifications:

Distributed load* w/ bottles: 132 lbs/ft²; 644kg/m² (528-22) **Distributed load* without bottles:** 109 lbs/ ft²; 532kg/m² (528-22)

Heat emission: 2,307 BTU/hr

 240 Model:
 240 Model w/ cart:

 40 1/4 in.; 103cm
 76 in.; 193cm

 52 in.; 132cm
 52 in.; 132cm

 30 3/4 in.; 78cm
 30 3/4 in.; 78cm

 656 lbs; 298kg
 1,158 lbs; 525kg

70 lbs/ft²; 339kg/m² (240-10) 59 lbs/ft²; 290kg/m² (240-10)

1,495 BTU/hr

*Distributed load refers to the force that the unit exerts across its 'footprint' (width x depth), measured in pound-force per square foot (kilogram-force per square meter).

Additional specifications (both models):

Clearance requirements: Environmental:

Front: 48 in.; 122cm Operating temperature: 59-82°F; 15-28°C
Rear: 4 in.; 11cm Humidity (non-condensing): 10-90%
Top: 24 in.; 61cm Operating elevation: 9,842 ft; 3,000m

Side: 4 in.; 11cm (maximum)

Electrical:

Line voltage: 100/110/220/240 vAC +/-10% Line frequency: 50/60 Hz +/-5%

Wattage: 800 watts (240-typical); 1000 watts (528-typical) **Certifications:** UL: 3101-1

115 lbs/ft²; 561kg/m² (240-10)

104 lbs/ft²; 508kg/m² (240-10)

1.495 BTU/hr

CSA: 22.2 No. 1010.1 IEC: 61010-1:90 + A1:92 + A2:95 IEC: 61326-1, 2002

Bottle capacity:

	Configuration:	# Drawers:	Max. annual bottle vol. 5-day blood culture	Max. annual bottle vol. 7-day blood culture	Max. annual bottle vol. Myco
240 Model:	96	4	7,000	5,000	850
	144	6	10,500	7,500	1,250
	192	8	14,000	10,000	1,700
	240	10	17,500	12,500	2,100
528 Model:	336	14	24,500	17,500	3,000
	384	16	28,000	20,000	3,500
	432	18	31,500	22,500	3,800
	480	20	35,000	25,000	4,300
	528	22	38,500	27,500	4,700

© 2011 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

USA and Canada +1 800 871 8909 **All Other Inquiries** +44 1342 318777

Technical Support

USA and Canada +1 800 642 7029 **All Other Inquiries** +44 1342 318777

